



FRONT MOTOR MOUNT COVER 1545

FITS: '91-UP DYNA MODELS EXCEPT CALIFORNIA MODELS WITH EMISSION CANISTER OR FXDWG AND FXDX WITH ENGINE GUARD FITS: '08-UP DRESSERS, ROAD KINGS, ROAD GLIDES, STREET GLIDES

PARTS INCLUDED

- 1 Motor Mount Cover, Chrome
- 2 3/8"–16 X 1-3/4" Socket Head Cap Screws
- 2 3/8" High Collar Split Lock Washers
- 2 3/8" Thick Flat Washers
- 1 Metal Reinforcement Plate
- 1 3/8"–16 X 2-1/2" Hex Head Cap Screw
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Set of standard Allen wrenches, torque wrench and a 7/16" open-end wrench.

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

PROCEDURE

- STEP 1** Remove the fastener labeled as "A" in PIC. 1. Replace it with a supplied 3/8"–16 X 2-1/2" Hex Head Cap Screw and torque to 35 foot-pounds.
- STEP 2** Remove the lower of the two OEM socket head cap screws that secure the front motor mount to the frame, labeled as "B" in PIC. 1. Replace it with a supplied 3/8"–16 X 1-3/4" Socket Head Cap Screw, 3/8" Thick Flat Washer and a 3/8" High Collar Split Lock Washer. Only start this fastener at this time.
- STEP 3** Remove the upper OEM socket head cap screw just above the one replaced in STEP 2.
- STEP 4** Insert the remaining supplied 3/8"–16 X 1-3/4" Socket Head Cap Screw, 3/8" Thick Flat Washer and 3/8" High Collar Split Lock Washer through the hole (not the slotted hole) in the Metal Reinforcement Plate and the upper hole in the Motor Mount Cover.

-cont.-

CUSTOMER SERVICE
877.370.3604 (toll free)

INSTALLATION QUESTIONS
techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY
Küryakyn warrants that any Küryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Küryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Küryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Küryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Küryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Küryakyn and a customer.
- Küryakyn products are often intended for use in specific applications. Küryakyn makes no warranty if a Küryakyn product is used in applications other than intended.
- Küryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Küryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Küryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Küryakyn. Küryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG
You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Küryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Küryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Küryakyn USA® All Rights reserved.



STEP 5 Hold the Motor Mount Cover in place. Slide the slotted hole in the cover and Metal Reinforcement Plate in between the motor mount and the fastener loosely installed in STEP 2.

STEP 6 Tighten the two 3/8"–16 X 1-3/4" Socket Head Cap Screws to 35 foot-pounds.

ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.

