



INSTALLATION

DAILY TOUR BAG

4133

PARTS INCLUDED

- 1 Daily Tour Bag
- 1 Shoulder Strap
- 1 "Y" Strap
- 2 8"x1" Hook and Loop Straps
- 2 Black Nylon Adjustable Straps with Metal Hooks
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND NOTICES REGARDING THE USE AND CARE OF THIS PRODUCT.



THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.



This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.



IF INSTALLING THIS PRODUCT FOR ANOTHER PARTY, PLEASE MAKE SURE THEY RECEIVE THIS COPY OF THE INSTALLATION INSTRUCTIONS SO THEY ARE AWARE OF THE IMPORTANT INFORMATION CONTAINED IN THEM.

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

- STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

PROCEDURE FOR MOUNTING/SECURING TO BACKREST

- STEP 2** To install the tour bag on a backrest, install the Y-strap as shown in PIC 1.



-cont.-

4133-23HD-1212

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
 - The product must be properly installed, maintained and operated under normal conditions.
 - Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
 - Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Kuryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.

- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

For purchasing Kuryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Kuryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.

kuryakyn.com



STEP 3 Place the Y-strap over the backrest and insert it through the lower D-ring, securing the hook and loop. PIC 2

STEP 4 Use the 8" straps and secure the bag around the arms of the backrest using the lower D-rings as shown in PIC 3.

STEP 5 If the backrest has a luggage rack, you also may use the additional straps on the front of the bag under the flap for additional security.

WARNING ALWAYS FOLLOW MANUFACTURER'S RECOMMENDATIONS ON YOUR LUGGAGE RACK FOR LOAD LIMITS. LOAD ONLY IN COMPLIANCE WITH YOUR VEHICLE OWNER'S MANUAL. OVERLOADING THE LUGGAGE RACK AND/OR MOTORCYCLE MAY CAUSE LOSS OF CONTROL RESULTING IN SERIOUS INJURY OR DEATH.

STEP 6 The additional straps are provided to provide additional securing options.

STEP 7 To use the shoulder strap, secure it to the D-rings on top of the bag.

NOTICE Secure all straps away from visible painted surfaces, moving parts, pinch points or extreme heat.

PROCEDURE FOR MOUNTING/SECURING TO TOUR-PAK LUGGAGE RACK OR SOLO LUGGAGE RACK

STEP 1 Place the bag on the rack and secure the bag to the rack using the straps that are under the flap on the front of the bag as shown in PIC 4.

STEP 2 Use the two 8" straps to secure the back of the bag to the rack as shown in PIC 5.

WARNING ALWAYS FOLLOW MANUFACTURER'S RECOMMENDATIONS ON YOUR TOUR-PAK AND/OR LUGGAGE RACK FOR LOAD LIMITS. LOAD ONLY IN COMPLIANCE WITH YOUR VEHICLE OWNER'S MANUAL. OVERLOADING THE LUGGAGE RACK AND/OR TOUR-PAK MAY CAUSE LOSS OF CONTROL RESULTING IN SERIOUS INJURY OR DEATH.

STEP 3 The additional straps are provided to provide additional securing options.

STEP 4 To use the shoulder strap, secure it to the D-rings on top of the bag.

NOTICE Secure all straps away from visible painted surfaces, moving parts, pinch points or extreme heat.

Ride On!

