

INSTRUCTIONS

-J00542 REV. 7-7-2003

Kit Number 51540-01A

DYNA GLIDE CUSTOM SEAT KIT

General

Kit Number 51540-01A is designed for installation on 1996 - 2003 Dyna Glide model motorcycles. **FXDWG models will require the separate purchase and installation of bracket number 52152-97.** This part is available for purchase from your Harley-Davidson Dealer.

See the Service Parts Illustration for a list of kit contents.

Installation

2

Grab strap

CAUTION

When performing the following procedures, be careful not to scratch painted surfaces (fender, tank, etc.) with metal tabs on seat.

- Remove existing seat from motorcycle. Keep lockwasher and screw
- 2. Remove existing grab strap and all attaching hardware.
- Install new grab strap onto motorcycle at same location old grab strap was removed (re-use existing hardware).
- On all models, except FXDWG, install existing stock rear bracket onto seat using stock hardware.

On FXDWG models, install the new rear bracket, 52152-97 onto the seat using the stock hardware.

51173-93

Position new seat on motorcycle. Be sure bracket on front of seat fully engages seat mounting tab on frame.

NOTE

On rear fenders of 1997 -2003 models, a captive nut secured with a plastic retention washer has replaced the previously used weld nut. Do not remove the plastic retention washer unless the captive nut is damaged and must be replaced. The plastic retention washer also prevents seat bracket from contacting paint on fender. Therefore, no nylon washer is required between bracket and fender on 1997 - 2003 models.

1996 DYNA MODELS ONLY

Secure seat with stock screw, stock lockwasher and place stock nylon washer between seat bracket and fender.

1997 - 2003 DYNA MODELS

Secure seat with stock screw and stock lockwasher.

AWARNING

After installing seat, pull upward on front of seat to be sure it is in locked position. While riding, a loose seat can shift causing loss of control, which could result in death or serious injury. (00070a)

generic style seat

