



# INSTRUCTIONS

-J00321

REV. 9-1-95

Kit Number 58248-96

## FLHT INNER FAIRING POUCH

### General

This kit is designed for installation on 1996 and later FLHT model motorcycles.

QTY	DESCRIPTION
-----	-------------

1	Pouch
1	Film strip

### Installation

1. Loosen 3 Torx screws located on front of fairing. Do not remove screws.
2. Pull outer fairing and windshield away from inner fairing to provide sufficient clearance to slide mounting bracket on bag between windshield and inner fairing.

3. Install clear static film on inside of windshield, centered on fairing center stud.
4. Position mounting bracket on bag over center stud. The pouch seats on ledge of inner fairing, flush with windshield and with opening facing rider.

#### CAUTION

To avoid damaging fairing, ensure that mounting bracket on pouch is flush with inner fairing before tightening Torx screws. If bracket is not flush with fairing, tightening screws could cause damage to fairing.

5. Tighten three Torx screws on front of outer fairing. Gently pull on bag to ensure that it is properly secured in place.



# INSTRUCTIONS

-J00321

REV. 9-1-95

Kit Number 58248-96

## FLHT INNER FAIRING POUCH

### General

This kit is designed for installation on 1996 and later FLHT model motorcycles.

QTY	DESCRIPTION
-----	-------------

1	Pouch
1	Film strip

### Installation

1. Loosen 3 Torx screws located on front of fairing. Do not remove screws.
2. Pull outer fairing and windshield away from inner fairing to provide sufficient clearance to slide mounting bracket on bag between windshield and inner fairing.

3. Install clear static film on inside of windshield, centered on fairing center stud.
4. Position mounting bracket on bag over center stud. The pouch seats on ledge of inner fairing, flush with windshield and with opening facing rider.

#### CAUTION

To avoid damaging fairing, ensure that mounting bracket on pouch is flush with inner fairing before tightening Torx screws. If bracket is not flush with fairing, tightening screws could cause damage to fairing.

5. Tighten three Torx screws on front of outer fairing. Gently pull on bag to ensure that it is properly secured in place.