



INSTRUCTIONS

-J01937

REV. 3-24-2004

Kit Number 62962-01, 62962-01A

CHROME OIL TEMPERATURE DIPSTICK FOR VRSC

General

This kit is designed for installation on 2002 and later VRSC Model Motorcycles.

There are no Service Parts in this kit.

NOTE

A Service Manual is available from your Harley-Davidson Dealer.

Installation and Removal

NOTE

If dipstick is not aligned properly after installing, follow instructions in the next section prior to installation.

1. Unscrew OE (Original Equipment) dipstick.
2. Install new dipstick and thread until it stops. Gently tighten.

Adjusting Dipstick for Direct Viewing

NOTE

The dipstick is designed to be adjusted so it can be viewed at a direct angle from the side. Perform the following:

- a. Install the dipstick and thread it in until it stops. Gently tighten.
- b. Using an erasable marker, mark the 12:00 position on the chrome bezel.
- c. Remove the dipstick. Back out each of the three Philips head screws one or two turns.
- d. Rotate the bezel and align the 200° degree mark on the readout portion of the gauge with the erasable mark made in Step b.
- e. Tighten each of the three Phillips screws securely and install dipstick.



INSTRUCTIONS

-J01937

REV. 3-24-2004

Kit Number 62962-01, 62962-01A

CHROME OIL TEMPERATURE DIPSTICK FOR VRSC

General

This kit is designed for installation on 2002 and later VRSC Model Motorcycles.

There are no Service Parts in this kit.

NOTE

A Service Manual is available from your Harley-Davidson Dealer.

Installation and Removal

NOTE

If dipstick is not aligned properly after installing, follow instructions in the next section prior to installation.

1. Unscrew OE (Original Equipment) dipstick.
2. Install new dipstick and thread until it stops. Gently tighten.

Adjusting Dipstick for Direct Viewing

NOTE

The dipstick is designed to be adjusted so it can be viewed at a direct angle from the side. Perform the following:

- a. Install the dipstick and thread it in until it stops. Gently tighten.
- b. Using an erasable marker, mark the 12:00 position on the chrome bezel.
- c. Remove the dipstick. Back out each of the three Philips head screws one or two turns.
- d. Rotate the bezel and align the 200° degree mark on the readout portion of the gauge with the erasable mark made in Step b.
- e. Tighten each of the three Phillips screws securely and install dipstick.